

## TECHNICAL DATA

### Accutron MR

---

#### Mechanical design

- Swivelling injection units connected to a mobile column stand
- Injection position at an angle of about 15° below horizontal, tilt vertically upwards to vent the system
- Total weight: 37 kg

#### Power supply

- Operation is independent of the mains supply, thanks to high-output rechargeable batteries
- Input voltage charger: 100 – 240 V, 50 – 60 Hz
- Power consumption charger: < 100 VA

#### Injection profiles

- 80 injection profiles can be edited and stored by the user

#### Filling of injection syringes

- Automatic filling via menu with volume input or manual filling with variable speed
- Filling speed: 1 – 5 ml/s
- Optimized tube systems with check valves

#### Injection parameters

##### Maximum injection pressure

- 200 ml

##### Partial injection volume

- 1 – 200 ml, programmable in 1 ml increment

##### Maximum injection pressure

- 21 bar, programmable from 5 to 21 bar in 1 bar increments

##### Flow rate of the two injection units

- 0.1 - 10 ml/s, programmable in 0.1 ml/s increments
- Alternatively, input of flow rate or phase duration

##### Number of phases

- 1 to 6

##### Injection delay

- 1 – 255 s

##### Phase delay

- 1 – 255 s

##### Remote control

- Wireless touch screen remote control
- Alternatively, display of injection parameters or pressure graph
- Optional: hand switch

Subject to technical alterations

